



# PAC250

## Portable Air-Cooled Aftercooler

---

### Equipment Features:



- High-efficiency portable aftercooler
- Ergonomically designed for carrying ease
- Oversized guard for improved air flow
- 7 Gauge carbon steel construction
- Chicago fitting provided on the inlet and outlet
- Heavy-duty 1-liter moisture separator
- Multiple manual drain valves for complete removal of captured fluids
- 50-foot power cord with alligator battery clips
- Cools air to within 15° of ambient temperature for optimal moisture removal

### Product Specifications:

- |                              |                                |
|------------------------------|--------------------------------|
| • RATED AIR FLOW             | 250 CFM                        |
| • MAXIMUM AIR FLOW           | 350 CFM                        |
| • MAXIMUM OPERATING PRESSURE | 250 psig                       |
| • MAXIMUM PRESSURE DROP      | 5 psig                         |
| • FAN POWER REQUIREMENT      | 22.2A @12V DC / 11.1A @ 24V DC |
| • DIMENSIONS                 | 36" W X 9.5" D X 29" H         |
| • WEIGHT                     | 60 lbs.                        |

### Options:

- Ball valves on Inlet/Outlet
- 120 AC power converter
- 2-prong and 4-prong Inlet/Outlet couplings ranging from 1/2" to 1-1/2"
- Power cord with ring terminal adaptors
- 12V or 24V Fan motors available